

**ALU-RACK YAMAHA FZS 600 Fazer**  
ALU-RACK YAMAHA FZS 600 Fazer

**Montagehinweise**

Alle vom Motorrad gelösten Schrauben sind gemäß Herstellerangaben wieder zu montieren, oder mit von SW-MOTECH gelieferten Schrauben zu ersetzen. Falls nicht anderweitig definiert, diese Schrauben nach Tabelle anziehen:

**M8 23 Nm**

Gegebenenfalls Schrauben mit flüssiger Schraubensicherung einkleben.

Prüfen Sie nach 50 km alle Verbindungen auf festen Sitz.

**Max. Zuladung 7,5 Kg inklusive Koffer und Adapter. Ist das Zuladungsgewicht des Fahrzeuges durch den Hersteller limitiert, gelten diese Grenzwerte.**

SW-MOTECH GmbH & Co. KG  
Ernteweg 8/10  
35282 Rauschenberg  
Germany

Tel. +49 (0) 64 25/8 16 8-00  
Fax +49 (0) 64 25/8 16 8-10

info@sw-motech.com  
www.sw-motech.com

**Mounting Instruction**

SW-MOTECH products should be installed by a qualified, experienced motorcycle technician. If you are unsure of your ability to properly install a product, please have the product installed by your local motorcycle dealer. SW-MOTECH takes no responsibility for damages caused by improper installation.

All screws, bolts and nuts, including all replacement hardware provided by SW-MOTECH, should be tightened to the torque specified in the OEM maintenance manual for your motorcycle. If no torque specifications are provided in the OEM maintenance manual, the following torques may be used:

**M8 23 Nm**

All screws, bolts and nuts should be checked after driving the first 50 km to ensure that all are tightened to the proper torque.

Medium strength liquid thread-locker (i.e., "Loctite") should be used to secure all screws, bolts and nuts.

**Max. Load On Rear Carrier: 7,5 Kg (16,5 lbs) inclusive case and adapter or the motorcycle manufacturer's weight limit, whichever is less.**

1 ALU-RACK  
ALU-RACK



schwarz/silber

GPT.o6.237.001 12

Anzahl/ Pcs. 1

5 Anschraubblech  
Support Bracket



GPT.o6.237.002 01

Anzahl/ Pcs. 2 (L/R)

6 Distanzbuchse  
Spacer



Da:18 Di:8,4 h:5

Anzahl/ Pcs. 2

7 Unterlegscheibe  
Washer



silber/silber

A 8,4 DIN 125

Anzahl/ Pcs. 2

2 Linsenkopfschraube  
Lenshead Screw



schwarz/silber

M8 x 16 ISO 7380

Anzahl/ Pcs. 4

3 Linsenkopfschraube  
Lenshead Screw



schwarz/black

M8 x 55 ISO 7380

Anzahl/ Pcs. 4

4 Distanzbuchse  
Spacer



Da:25 Di:12,5 h:28

Anzahl/ Pcs. 4

