SV650 FAIRING LOWERS

FITTING KIT:

- 4 x M4 x 16mm Flange headed bolt
- 4 x M4 Rubber well nut
- 4 x M5 Plastic washers
- 2 x M6 Lug nut
- 4 x M6 x 16mm Flange Headed bolt
- 4 x M6 Plastic washers
- 2 x M6 Rubber washers
- 2 x M6 counter sunk washer
- 2 x M6 x 25mm Counter sunk bolt
- 1 x Left front bracket (a)
- 1 x Left rear bracket (b)
- 1 x Right front bracket (c)
- 1 x Right rear bracket (d)









FITTING INSTRUCTIONS:

- 1. Remove lower bolts from radiator cover and attach both front left and right brackets using existing bolts (a,c) (do not tighten)
- 2. Remove bolts from engine casing on both sides and fit both rear brackets on the left and right hand side (b,d) using existing bolts, you are ok to tighten these.
- 3. Insert the 4 x M4 rubber well nuts into front of the centre panel and insert the 2 x M6 luq nuts into the bottom
- 4. Fit the right hand panel to the bottom panel using 2 of the M4 x 16mm flange headed bolts with 2 of the M5 plastic washers and 1 of the M6 Flange headed bolts with M6 plastic washer
- 5. Remove the upper fairing bolt and place right hand lowers in-between the upper fairing and mounting bracket then replace the bolt (do not tighten)
- 6. Attach the fairings on the right to the front bracket using $1 \times 10^{10} \times 10^{10}$ x M6 x 25mm counter sunk bolt, 1×10^{10} x M6 counter sunk washer and 1×10^{10} of the M6 rubber washers (do not tighten)
- 7. Attach the fairings on the right side rear brackets using the M6 x 16mm flange headed bolt, (do not tighten)
- 8. Repeat steps 5, 6, and 7 on left hand side and attach to centre panel
- 9. Once happy with fit tighten bolts all round